

19214
43257

Paola

Air Conditioning Engineering

Fourth Edition

W.P. Jones

MSc, CEng, FInstE, FCIBSE, MASHRAE

105048



A member of the Hodder Headline Group
LONDON • SYDNEY • AUCKLAND

Only for sale in the Indian Sub-continent,
South East Asia, Africa and the Caribbean



Contents

1. The Need for Air Conditioning	1
1.1 The meaning of air conditioning	1
1.2 Comfort conditioning	1
1.3 Industrial conditioning	2
2. Fundamental Properties of Air and Water Vapour Mixtures	4
2.1 The basis for rationalisation	4
2.2 The composition of dry air	4
2.3 Standards adopted	6
2.4 Boyle's law	7
2.5 Charles' law	8
2.6 The general gas law	10
2.7 Dalton's law of partial pressure	12
2.8 Saturation vapour pressure	13
2.9 The vapour pressure of steam in moist air	14
2.10 Moisture content and humidity ratio	17
2.11 Percentage saturation	19
2.12 Relative humidity	20
2.13 Dew point	21
2.14 Specific volume	22
2.15 Enthalpy: thermodynamic background	23
2.16 Enthalpy in practice	24
2.17 Wet-bulb temperature	26
2.18 Temperature of adiabatic saturation	29
2.19 Non-ideal behaviour	31
2.20 The triple point	34
3. The Psychrometry of Air Conditioning Processes	39
3.1 The psychrometric chart	39
3.2 Mixtures	40
3.3 Sensible heating and cooling	43
3.4 Dehumidification	45
3.5 Humidification	49
3.6 Water injection	53
3.7 Steam injection	55
3.8 Cooling and dehumidification with reheat	57
3.9 Pre-heat and humidification with reheat	63

3.10	Mixing and adiabatic saturation with reheat	67
3.11	The use of dry steam for humidification	69
3.12	Supersaturation	71
3.13	Dehumidification by sorption methods	72
4.	Comfort and Inside Design Conditions	78
4.1	Metabolism and comfort	78
4.2	Bodily mechanisms of heat transfer and thermostatic control	79
4.3	Metabolic rates	80
4.4	Clothing	81
4.5	Environmental influences on comfort	83
4.6	Other influences on comfort	85
4.7	Fanger's comfort equation	86
4.8	Synthetic comfort scales	87
4.9	Measuring instruments	89
4.10	Environmental freshness	90
4.11	The choice of inside design conditions	91
5.	Climate and Outside Design Conditions	98
5.1	Climate	98
5.2	Winds	99
5.3	Local winds	100
5.4	The formation of dew	101
5.5	Mist and fog	101
5.6	Rain	103
5.7	Diurnal temperature variation	104
5.8	Diurnal variation of humidity	105
5.9	Meteorological measurement	107
5.10	The seasonal change of outside psychrometric state	110
5.11	The choice of outside design conditions	112
6.	The Choice of Supply Design Conditions	117
6.1	Sensible heat removal	117
6.2	The specific heat capacity of humid air	120
6.3	Latent heat removal	121
6.4	The slope of the room ratio line	123
6.5	Heat gain arising from fan power	129
6.6	Wasteful reheat	130
6.7	The choice of a suitable supply state	133
6.8	Warm air supply temperatures	138
7.	Heat Gains from Solar and Other Sources	141
7.1	The composition of heat gains	141
7.2	The physics of solar radiation	141
7.3	Sky radiation	142
7.4	Definitions	143
7.5	The declination of the sun	145
7.6	The altitude of the sun	147
7.7	The azimuth of the sun	149
7.8	The intensity of direct radiation on a surface	150
7.9	The numerical value of direct radiation	153

7.10	External shading	156
7.11	The geometry of shadows	156
7.12	The transmission of solar radiation through glass	158
7.13	The heat absorbed by glass	160
7.14	Internal shading and double glazing	162
7.15	Numerical values of scattered radiation	165
7.16	Minor factors influencing solar gains	166
7.17	Heat gain through walls	172
7.18	Sol-air temperature	174
7.19	Calculation of heat gain through a wall or roof	175
7.20	Air conditioning loads due to solar gain through glass	179
7.21	Heat transfer to ducts	189
7.22	Infiltration	192
7.23	Electric lighting	193
7.24	Occupants	195
7.25	Power dissipation from motors	196
7.26	Business machines	197
8.	Cooling Load	206
8.1	Cooling load and heat gains	206
8.2	Cooling load for a whole building	209
8.3	Partial load	209
8.4	Cooling load offset by reheat	210
8.5	The use of by-passed air instead of reheat	215
8.6	Face and by-pass dampers	217
8.7	Cooling in sequence with heating	219
8.8	Hot deck-cold deck systems	220
8.9	Double duct cooling load	220
8.10	The load on air-water systems	222
8.11	Diversification of load	224
8.12	Load diagrams	224
9.	The Fundamentals of Vapour Compression Refrigeration	231
9.1	The basis of vapour compression refrigeration	231
9.2	Thermodynamics and refrigeration	233
9.3	The refrigerating effect	238
9.4	The work done in compression	239
9.5	Heat rejected at the condenser	241
9.6	Coefficient of performance	242
9.7	Actual vapour compression cycle	246
9.8	Pressure-volume relations	249
9.9	Volumetric efficiency	253
9.10	Thermosyphon cooling	255
9.11	Refrigerants	255
9.12	Ozone depletion effects	258
9.13	Safety	259
10.	Air Cooler Coils	263
10.1	Distinction between cooler coils and air washers	263
10.2	Cooler coil construction	264
10.3	Parallel and contra-flow	268
10.4	Contact factor	269
10.5	Heat and mass transfer to cooler coils	273

10.6	Sensible cooling	278
10.7	Partial load operation	282
10.8	The performance of a wild coil	284
10.9	Sprayed cooler coils	285
10.10	Free cooling	287
10.11	Direct-expansion coils	288
10.12	Air washers	288
11.	The Rejection of Heat from Condensers and Cooling Towers	295
11.1	Methods of rejecting heat	295
11.2	Types of cooling tower	296
11.3	Theoretical considerations	299
11.4	Evaporative condensers	301
11.5	Air-cooled condensers	301
11.6	Automatic control	302
11.7	Practical considerations	304
12.	Refrigeration Plant	309
12.1	The expansion valve	309
12.2	The distributor	313
12.3	Float valves	313
12.4	Evaporators for liquid chilling	314
12.5	Direct expansion air cooler coils	316
12.6	The reciprocating compressor	319
12.7	The air-cooled condensing set	321
12.8	Condensing set–evaporator match	322
12.9	The control of direct-expansion cooler coils and condensing sets	323
12.10	The performance of water chillers	325
12.11	The screw compressor	331
12.12	The scroll compressor	334
12.13	Centrifugal compressors	335
12.14	The water-cooled condenser	340
12.15	Piping and accessories	342
12.16	Charging the system	343
13.	Automatic Controls	345
13.1	The principle of automatic control	345
13.2	Definitions	346
13.3	Measurement and lag	348
13.4	Measurement elements	349
13.5	Types of system	352
13.6	Methods of control	355
13.7	Simple two-position control	356
13.8	Timed two-position control	356
13.9	Floating action	356
13.10	Simple proportional control	358
13.11	Refined proportional control	360
13.12	Automatic valves	362
13.13	Automatic dampers	371
13.14	Application	373
13.15	Fluidics	376
13.16	Control by microprocessors	376

14. Vapour Absorption Refrigeration	380
14.1 Basic concepts	380
14.2 Temperatures, pressures, heat quantities and flow rates for the lithium bromide-water cycle	381
14.3 Coefficient of performance and cycle efficiency	386
14.4 Practical considerations	388
14.5 Other absorption systems	389
15. Airflow in Ducts and Fan Performance	392
15.1 Viscous and turbulent flow	392
15.2 Basic sizing	396
15.3 Conversion from circular to rectangular section	399
15.4 Energy changes in a duct system	401
15.5 Velocity (dynamic) pressure	403
15.6 The flow of air into a suction opening	404
15.7 The coefficient of entry (C_E)	405
15.8 The discharge of air from a duct system	406
15.9 Airflow through a simple duct system	407
15.10 Airflow through transition pieces	408
15.11 Airflow around bends	414
15.12 Airflow through supply branches	418
15.13 Flow through suction branches	419
15.14 Calculation of fan total and fan static pressure	419
15.15 The interaction of fan and system characteristic curves	425
15.16 The fan laws	427
15.17 Maximum fan speed	429
15.18 Margins	429
15.19 Power-volume and efficiency-volume characteristics	430
15.20 Fan testing	434
15.21 The performance of air handling units	435
15.22 Methods of varying fan capacity in a duct system	437
15.23 The effect of opening and closing branch dampers	441
15.24 Fans in parallel and series	444
16. Ventilation and a Decay Equation	450
16.1 The need for ventilation	450
16.2 The decay equation	458
16.3 An application of the decay equation to changes of enthalpy	465
17. Filtration	472
17.1 Particle sizes	472
17.2 Particle behaviour and collection	473
17.3 Efficiency	474
17.4 Classification according to efficiency	478
17.5 Viscous filters	479
17.6 Dry filters	480
17.7 Electric filters	482
17.8 Wet filters	484
17.9 Centrifugal collectors	485
17.10 Adsorption filters	485
17.11 Safety	486
Index	489

Index

- Abrupt expander, 409
- Abrupt reducer, 413
- Absenteeism, 92
- Absolute filters, 475, 480
- Absolute roughness, 393, 395
- Absolute temperature, 9, 10, 11, 234
- Absolute viscosity of air, 395
- Absorbent, 380
- Absorber, 380, 381, 382, 385, 386, 390
- Absorption, 484
- Absorption dehumidification, 72-74
- Absorptivity of glass, 159
- Accuracy of control, 348, 349
- Acoustic coagulation, 474
- Acrolein, 451
- Activated carbon filter, 486
- Adiabatic compression, 249, 402
- Adiabatic cooling, 51-53, 67-69, 103
- Adiabatic lapse rate of temperature, 103
- Adiabatic process, 234
- Adiabatic saturation, 51-53, 67-69, 263
- Admittance, 187
- Adsorption dehumidification, 74-75
- Adsorption filters, 485-486
- Advection fog, 102
- Aerofoil section blades, 432, 433
- Aerosols, 473
- Agglomerated flakes (of dust), 484
- Air
 - distribution performance index, 84
 - handling units, 433, 435-436
 - leakage, 429
 - mass, 167
 - point control factor, 188
 - power, 129, 401
 - pressure drop rate, 392-396
 - temperature rise in a duct system, 401-402
 - velocity, 83-84, 91
 - washers, 263, 264, 288-290, 484, 485
 - temperature, 91-92
- Air conditioning, 1
- Air-cooled condensers, 295, 296, 301-302, 321
- Air-cooled condensing set, 321-325
- Air-water systems, 222-224
- Altitude of the sun, 143, 147-148
- Ammonia, 389-390
- Angle factor, 102, 165
- Apparatus dew point, 46
- Aqua-ammonia vapour absorption system, 389-390
- Argon, 6
- Arrestance, 476-478
- Aspect ratio of ducts, 399, 414-418
- Aspirated wet-bulb temperature, 27
- Asymmetrical valve characterisation, 370
- Asymmetry of thermal radiation, 85
- Atmospheric dust spot efficiency, 475-478
- Atmospheric haze, 167
- Authority of a valve, 363-367, 370
- Automatic controller, 347
- Automatic dampers, 371-373
- Automatic roll filter, 476, 479, 480, 482
- Automatic valves, 362-370
- Automatic viscous filter, 479, 480
- Average atmospheric dust spot efficiency, 477
- Avogadro's hypothesis, 10, 11
- Axial flow fan, 431, 434
- Azimuth of the sun, 143, 149-150
- Back pressure valve, 325, 326
- Backward curved impeller, 425, 432, 433
- Bacteria, 473
- Balancing relay, 354-355
- Barometric pressure, 6, 27
- Baudelot cooler, 314
- Bends, 414-418
- Bends in series, 416
- Bernoulli's theorem, 400, 402, 406
- Bimetallic strip, 346, 349
- Bioeffluents from people, 455, 456
- Blow-through cooler coils, 267, 268
- Body odour, 452, 457, 486
- Body surface temperature, 79-80
- Bourdon tube, 350
- Boyle's law, 7, 8, 10
- Boyle temperature, 8

- Branch dampers, 441–444
- Break tanks for cooling towers, 305
- Brownian motion, 473
- Business machines, 197–198
- Butterfly damper, 371
- By-passed air, 215–217
- By-pass factor, 47

- Capacity index for a valve, 370
- Capillary condensation, 474
- Carbon dioxide, 6, 91, 450, 452, 455, 456, 458–463
- Carbon monoxide, 451, 464–465
- Carnot coefficient of performance, 242–245
- Carnot cycle, 242
- Cavitation, 304, 306
- Centrifugal collectors, 485
- Centrifugal compressor, 256, 335–340
- CFCs, 258–259
- Characterised valves, 365–367
- Charging point, 343
- Charles' law, 7, 8, 9, 10, 350
- Chilled water return temperature, 312
- Chilled water storage, 330–331
- Chinook wind, 101
- CIBSE standard weather year, 109–110
- Cigarette smoke, 452–453
- Circular to rectangular conversion, 399–400
- Circulatory losses, 336
- Classification according to efficiency, 478–479
- Climate, 98–114
- Closed loop, 345, 346, 347
- Closed thermodynamic system, 233
- Cloth ducting, 396
- Clothing, 81–83
- Cloud cover, 102
- Clo-values, 81–82
- Coefficient for an abrupt expander, 409
- Coefficient for a gradual expander, 409
- Coefficient of area, 405–406
- Coefficient of entry, 405–406
- Coefficient of friction, 392, 393, 394
- Coefficient of performance, 242–245, 386–388
- Coefficient of velocity, 405–406
- Colbrook White function, 393
- Cold radiation, 85
- Collection unit, 483
- Compression ratio, 254, 312
- Comfort conditioning, 1
- Comfort, 78–92
- Common cold, 92
- Compensated control, 346
- Compression
 - efficiency, 254
 - ratio, 253, 312, 339
- Compressor, 231, 234, 319–321
 - characteristics, 319–320
 - lubrication, 321
- Condensate drain trays, 265–267
- Condensation nuclei, 101
- Condenser, 231, 340–341, 380, 381, 385, 386, 390
- Condensing pressure, 249–253, 310, 312
- Condensing pressure control, 302–304
- Contact factor, 47, 132, 134, 136, 269–273, 282
- Contra-flow heat exchange, 265, 268, 270
- Controlled variable, 346
- Controller, 346, 359
- Control of vapour absorption systems, 389
- Control point, 346
- Convective heat loss from the body, 79
- Conversion from circular to rectangular ducts, 399–400
- Cooler coil
 - cabinet, 435, 436
 - characteristics, 317–319
 - construction, 264–268
 - face velocity, 267
 - fin spacing, 262, 267
 - selection, 134
- Cooling in sequence with heating, 219–220
- Cooling load, 130–133, 206–229
 - analysis, 130–133, 206–209
 - check, 206–209
 - for a whole building, 209
 - offset by re-heat, 210–215
- Cooling towers, 287, 296–301
 - cross-flow, 296, 298
 - forced draught, 296, 298
 - induced draught, 296
 - bleed rate, 304–305
 - break tanks, 305
- Corrected effective temperature, 87, 89
- Critical speed, 429
- Critical temperature, 4, 5
- Cross-virial coefficients, 14
- Crystallisation, 389
- Curvature of a bend, 415
- Curve ratio, 416
- Cycle efficiency, 386–388
- Cycling, 347
- Cyclones, 100, 485
- Cylinder unloading, 320, 324–330

- Dalton's law of partial pressure, 4, 7, 12, 17, 20, 22, 31
- Dampers, 371–373
- Deadtime, 348
- Decay equation, 458–465
- Decipol, 454
- Declination of the sun, 143, 145–147
- Decrement factors, 176–179
- Dehydration of refrigeration systems, 343

- Dehydrator, 343
- Dehumidification, 45–49, 57–63, 72–75, 265
- Density of air, 6, 12
- Density of water, 6
- Derivative action, 360–361
- Derivative control, 360–361
 - factor, 361
- Desiccation, 72–75
- Desired value, 346
- Deviation, 346, 360–361
- Dew
 - evaporation, 106
 - formation, 101
 - point, 21, 22, 105–106, 167–168
 - point measurement, 351
- Differential, 347
 - gap, 347
- Diffuse radiation, 142–143, 155, 165–166
- Diffusion, 473
- Direct action, 359
- Direct digital control, 377
- Direct expansion cooler coils, 288, 316–319
- Direct radiation, 154
- Discolouration tests, 474
- Disc throttling, 441
- Distributor, 265, 310, 313, 325
- Diurnal variation
 - of humidity, 105–107
 - of temperature, 100, 104–105
- Diversification of load, 224
- Diversity factors, 198, 209
- Doldrums, 99–100
- DOP test, 475
- Double duct systems, 220, 223
- Double glazing, 158, 160–165
- Double seat valves, 368
- Draw-through cooler coils, 267–268
- Drift, 349
- Drift eliminators, 295
- Dry air, 4
- Dry-bulb temperature, 39, 83, 89, 90, 91
- Dry cooler, 287
- Dry evaporators, 314, 316
- Dry filters, 480–482
- Dryness fraction, 235
- Dry resultant temperature, 89
- Dry saturated vapour, 235
- Dry steam humidifiers, 212
- Du Bois surface area, 81
- Duct aspect ratio, 399, 414–418
- Duct heat gain, 135, 189–192
- Duct sizing chart, 394
- Dust holding capacity, 477–478
- Dusts, 472
- Dynamic differential, 347
- Dynamic pressure, 403
- Earth temperatures, 113
- Economisers, 334
- Effective temperature, 87
- Efficiency-volume fan characteristics, 430–431
- Electrical control system, 354–355
- Electric filters, 482–484
- Electronic control system, 355
- Electronic expansion valve, 311–313
- Electrostatic filters, 474
- Emissions from room furnishings, 455
- Energy, 233
 - kinetic, 233
 - potential, 233
 - stored, 233
 - transient, 233
- Enthalpy, 23–26, 33–39
 - gain to a room, 466–468
 - measurement, 351
- Entropy, 233
- Entry loss, 405, 406–408
- Environmental temperature, 89, 187
- Equal percentage valve characterisation, 366–367
- Equal pressure drop method of duct sizing, 398
- Equivalent temperature, 87
- Erosion of tubes, 315
- Escape corridors, 458
- Escape staircases, 458
- Etoile airflow straightener, 434
- EU values, 478–479
- Eurovent standard, 475
- Eurovent 4/4, 488
- Eurovent 4/5, 477, 478
- Evaporating pressure, 249–253, 309, 311, 312
- Evaporative condenser, 295, 296, 297, 301
- Evaporative cooling, 263
- Evaporative heat loss, 79
- Evaporator, 231, 314–319, 380, 381, 386, 390
- Expanders, 408–411
- Expansion engine, 234, 242, 245
- Expansion valve, 231, 246, 309–313, 380, 390
 - rating, 309–311
 - sizing, 311
- Exponential decay, 459, 460
- External resistance, 436
- External shading, 156
- Extract duct systems, 396
- Extract ventilated light fittings, 195
- Face and by-pass dampers, 217–219
- Face control of direct expansion coils, 324
- Face velocity for cooler coils, 267
- Fan
 - cabinet, 435, 436
 - coil units, 223
 - laws, 427–429

- Fan, *continued*
 power, 130, 131, 133, 401, 427–428
 power heat gain, 129–130, 135
 speed variation, 437
 static pressure, 403, 419–425, 435
 testing, 434–435
 total pressure, 401–403, 419–425, 427–428
- Fan characteristic curves, 425, 431
- Fanger's comfort equation, 86
- Fanning equation, 392
- Fanning friction factor, 362
- Fans in parallel and series, 444–445
- Filtration, 472–486
- Final control element, 347
- Fin spacing for cooler coils, 267
- First law of thermodynamics, 23, 233
- Flat oval ducts, 400
- Flexible ducts, 395, 396
- Floating action, 356–358
- Floating control, 355, 356–358
- Float valves, 313–314
- Flooded evaporators, 314–316
- Floor temperatures, 84–85
- Flow coefficient for a valve, 370
- Fluidics, 376
- Foaming, 321
- Fog, 101–102, 472
- Forced draught cooling towers, 296–299
- Forward curved impeller, 431, 432
- Fouling factors, 315, 341
- Free cooling, 287–288
- Freeze-up, 315
- Frequency inverter, 437
- Frequency of occurrence of outside temperature, 109–110
- Fresh air
 load, 131, 133, 209
 requirements, 91, 450, 453, 458
- Friction factor, 394
- Frictional loss past a grille, 406–407
- Fumes, 472
- Fungi spores, 473
- Garage ventilation, 464–465
- Gases, 4, 473
- Gas filled thermometer, 350
- Gauges, 342
- Gauge glasses, 342
- General gas law, 6, 10, 17
- Generator, 380, 381, 382, 385, 386, 387, 390
- Geometry of shadows, 156–158
- Glass temperature, 162
- Globe thermometer, 89, 90
- Glycol in chilled water, 315
- Gradual expander, 409, 410
- Gradual reducer, 413, 414
- Gravimetric tests, 475
- Gravitational separation, 473
- Gravity wind, 101
- Ground radiation, 166, 170–171
- Ground temperatures, 113
- Hallide torch, 343
- Haze, atmospheric, 167, 170
- HCFCs, 259
- Heat, 233
 absorbed by glass, 160–162
 exchanger, 388, 390
 gain from electric lighting, 193–195
 gain from occupants, 195–196
 gain to ducts, 189–192
 gain through walls and roofs, 172–179
 gain from business machines, 197–198
 gain from electric motors, 196
 gain from fan power, 129–130
 islands, 113
 rejected at the condenser, 241
 stress index, 80
- Heat-absorbing glass, 163
- Heat-reflecting glass, 163–164
- Heavyweight buildings, 181, 184, 187
- Height above sea level, 154, 167
- HEPA filters, 480
- Hermetic compressors, 320
- HFCs, 259
- High efficiency particulate air filters, 480
- Highest barometric pressure, 100
- High pressure cut-out setting, 340
- High-side float valve, 313
- High velocity duct systems, 396
- Hot deck–cold deck systems, 220, 222
- Hot gas
 header, 325, 326
 valve, 325, 326
- Hour angle, 145
- Human hair, 472
- Human oxygen consumption, 90–91
- Humidification, 49–53, 63–67, 212, 214, 264
- Humidifier fever, 263
- Humidifying efficiency, 49, 285
- Humidity
 measurement, 351
 ratio, 17
- Humid volume, 39, 40
- Hunting, 347
- Hydraulic control system, 353
- Hydraulic diameter, 393
- Hydrogen, 6
- Hygroscopic material, 380
- Ice point, 34
- Ideal gas laws, 4, 7, 31
- Illuminance, 194
- Impaction, 474

- Impeller tip speed, 338–339
- Impingement, 474
- Increasing valve sensitivity, 365
- Index duct run, 398
- Induced draught cooling towers, 296–301
- Induction units, 223
- Industrial conditioning, 2, 212
- Inertia of the building, 180
- Inertial separation, 474, 479
- Infiltration heat gains, 192–193
- Inherent damper characteristic, 371
- Insensible perspiration, 79
- Inside design conditions, 91–92
- Insolation, 98, 99
- Installed damper characteristic, 371
- Instantaneous solar gain, 181
- Integral action, 360–361
- Integral control, 360–361
- Integral control factor, 361
- Intensity of direct solar radiation, 150–156, 170
- Intensity of direct radiation on a surface, 150–153
- Intensity of sky radiation, 166, 170
- Interaction coefficients, 14, 32, 33
- Interception, 474
- Intercooling, 339
- Interlaced cooler coils, 324
- Intermolecular forces, 14, 23, 31
- Internal energy, 23
- Internal shading, 162–165
- Ionising unit, 483
- Ionising voltage, 483
- Isentropic adiabatic efficiency, 254
- Isentropic process, 234
- Isentropic compression, 249

- Katabatic wind, 101
- Kata thermometer, 89, 90
- Kinetic energy, 233
- Kinetic energy loss from a system, 407–408
- Kinetic theory of gases, 7, 12, 14, 31

- Latent heat gain, 193, 195–196
- Latitude, 98, 144
- Leaks from refrigeration systems, 343
- Legionnaires' Disease, 306–307
- Lewis number, 28–31
- Lighting heat gain, 193–195
- Lightweight buildings, 181, 184, 187
- Liquid
 - expansion thermometer, 350
 - receiver, 304
- Lithium
 - bromide, 380, 381
 - bromide-water cycle, 381–386, 388
 - chloride, 72–74

- Load
 - diagrams, 224–228
 - diversification, 224
- Local winds, 100–101
- Logarithmic mean temperature difference, 265, 271, 273
- Longitude, 144
- Long-term occupancy, 92
- Lowest barometric pressure, 100
- Lowest possible percentage dissatisfied, 87
- Low-side float valve, 313–314
- Low velocity duct systems, 396
- Lubrication of compressors, 321, 332, 342

- Margins, 429
- Maximum fan speed, 429
- Maximum working pressure, 340
- Mean coil surface temperature, 46
- Mean daily maximum temperature, 104–110
- Mean daily minimum temperature, 104–110
- Mean hydraulic diameter, 393
- Mean radiant temperature, 83, 85, 91
- Measurement and lag, 348–349
- Measuring instruments, 89–90
- Mechanical efficiency, 254
- Medium velocity duct systems, 396
- Metabolic rates, 80–81, 90, 91
- Metabolism, 78
- Meteorological measurement, 107–110
- Methylene blue dye, 475
- Microprocessor control, 376–378
- Minimum controllable flow, 367
- Mist, 101–102, 472
- Mistral, 101
- Mixtures, 40–43
- Moisture content, 17, 18, 31, 39
- Molecular mass, 6, 11, 31
- Mole fraction, 32
- Monsoons, 100
- Moody friction factor, 362
- Motor burn-out, 320
- Motorised expansion valve, 311
- Multi-leaf dampers, 371
- Multi-zone units, 222

- Natural cooling capacity of the outside air, 210
- Negative feedback, 346
- Negative ions, 91, 483
- New effective temperature, 87, 88
- Nitrogen, 6
- Noise break-out from flexible ducts, 396
- No-loss entry, 405
- Non-ideal behaviour, 31–34

- Odours, 450, 485–486
- Offset, 346, 361

- Oil pressure failure switch, 342
- Oil separator, 342
- Olf, 454
- Opacity meter, 475
- Open loop, 346
- Open thermodynamic system, 233
- Operative temperature, 80, 88, 89
- Opposed blade dampers, 371–373
- Organic particles, 472
- Outside design conditions, 112–114
- Overshoot, 347, 357
- Oxygen, 6
 - consumption of a human, 90–91
- Ozone depletion factors, 258–259

- Parallel blade dampers, 371–373
- Parallel-flow heat exchange, 268–269
- Partial load, 209–210, 281–284
- Partial pressure, 12, 20–32
- Particle
 - collection, 473–474
 - sizes, 472–473
- Particular gas constant, 6, 11
- Path length of solar radiation, 167
- Penetration, 475
- Perceived indoor air quality, 454, 455, 456
- Perceived outdoor air quality, 454, 456
- Percentage
 - dissatisfied people, 86, 454, 455
 - saturation, 19, 20, 23, 31, 39, 40
- Permeable cloth ducting, 396
- Pin-hole leaks, 474
- Piping and accessories for refrigeration, 342
- Plane radiant temperature, 85
- Plate heat exchangers, 316, 341
- Pneumatic control system, 352–353
- Poiseuille formula, 393
- Pollen, 473
- Polytropic compression, 249, 251
- Polytropic efficiency, 251
- Polytropic head, 251
- Pollution concentration, 454
- Population density, 196
- Positioners, 370
- Positive ions, 483
- Potential correction, 360
- Potential energy, 233
- Potential value, 359–360
- Power-volume fan characteristics, 430–432
- Precision, 349
- Predicted mean vote, 86
- Predicted percentage dissatisfied, 86
- Pre-heat, 63–67
- Pressure,
 - drop correction factors for duct materials, 395
 - equalising line, 310–311
 - gauges, 342
- Pressure-volume fan characteristics, 425–434
- Primary element, 346
- Properties of Refrigerant 22, 236–237
- Proportional band, 347, 359, 360
- Proportional control, 358–360
- Proportional control factor, 360
- Psychrometric chart, 39, 40
- Psychrometric equation, 27
- Pull-down load, 181, 184

- Radiant temperature asymmetry, 85
- Radiation fog, 102
- Radiative heat loss from the body, 79–80
- Radon emission, 457
- Rain, 103
- Raindrop sizes, 473
- Rangeability, 370
- Rating of expansion valves, 309–310
- Reciprocating compressor, 256, 338
- Rectifier, 389, 390
- Reducers, 412–414
- Refined proportional control, 360–361
- Reflective curtains, 165
- Reflective plastic films, 164–165
- Reflectivity of glass, 158
- Refrigerant, 231, 380, 381, 382, 388
 - leak testing, 343
- Refrigerants, 255–257
- Refrigerant 22
 - properties of, 236–237
- Refrigerating effect, 238
- Refrigeration
 - lubrication, 342
 - piping and accessories, 342
- Regulating valve, 369–370
- Regulator, 359
- Re-heat, 57–63, 130–133
- Relative humidity, 19–21, 83–84, 91–92, 105–107, 109
- Relative roughness, 393
- Repeatability, 349
- Resistance thermometer, 350
- Resultant temperature, 87, 89
- Reverse action, 359
- Reversible cycle, 386
- Reversibility, 234
- Reversible engine, 234
- Reynolds number, 392
- Roof heat gain, 172–179
- Room ratio line, 123–129
- Roughness
 - absolute, 393
 - relative, 393
- Safety, 259, 340, 486
- Salt, 101

- Saturated liquid, 15, 234
- Saturated vapour, 15
- Saturation temperature, 14
- Saturation vapour pressure, 13, 14, 18, 27, 383
- Scattered radiation, 142–143, 155, 165–166
- Schematic diagrams, 372, 374–375
- Screened wet-bulb temperature, 107
- Screw compressor, 331–334
- Scroll compressor, 334–335
- Seasonal variation of outside psychrometric state, 110–112
- Seasonal variation of temperature, 100
- Second law of thermodynamics, 233
- Sensitivity, 349
- Sensory pollution load, 454
- Self-acting control system, 352
- Set point, 346, 347
- Shading, 156–158, 184
 - coefficient, 162
 - factor, 188
- Shadow cast on a window, 157
- Shell-and-coil condensers, 341
- Shell-and-tube
 - condensers, 340–341
 - evaporators, 314–315
- Shock effect, 86
- Short-term occupancy, 92
- Sick Building Syndrome, 452
- Sight glasses, 342
- Simple proportional control, 358–360
- Simple saturation refrigeration cycle, 232, 244
- Single seat valves, 368
- Skin temperatures, 80
- Sky radiation, 142–143, 155, 165–166, 170
- Sling psychrometer, 89–90
- Sling wet-bulb temperature, 27, 39, 107
- Smells, 486
- Smokes, 473
- Smoking and ventilation, 450–453, 457
- Smoking intensity, 457
- Sodium flame test, 478
- Sol-air temperature, 174–175
- Solar gain storage load factors, 186
- Solar gain through glass, 179–189
- Solar gain through glass and building thermal inertia, 180
- Solar gain through glass and pull-down load, 181, 184
- Solar radiation, 98
- Solar spectrum, 142
- Solar transmission through glass, 158–160
- Solenoid valves, 342
- Sorption methods, 72–75
- Southern hemisphere solar radiation, 156, 168
- Southern hemisphere solar altitude and azimuth, 149–150
- Specific entropy, 234
- Specific heat of humid air, 120–121
- Specific humidity, 17, 39
- Specific volume, 12, 22, 23, 32
- Spirally-wound ducts, 400
- Splitters, 416–417
- Sprayed cooler coil, 284–287
- Standards, 6
- Standard effective temperature, 87, 88
- Standard temperature and pressure, 7
- State point, 39
- Static differential, 347
- Static pressure, 39, 401, 433
- Static regain, 409, 410, 412, 433
- Static regain duct sizing, 399, 411–412
- Steam, 5, 6
 - consumption for absorption refrigeration, 387, 389
 - injection, 55–57, 69–71
 - point, 34
 - pressures for vapour absorption systems, 389
- Static suction, 407–408
- Storage load factors for solar gain, 186
- Stored energy, 233
- Strainers, 306, 342
- Sub-cooled liquid, 235, 246, 341
- Submerged evaporator, 313, 314
- Suction branches, 419
- Suction line sizing, 322
- Suction opening, 404–405
- Suction pressure, 322–323
- Sulphur dioxide, 102
- Sun time, 145
- Superheat setting for expansion valves, 309–313
- Superheated vapour, 235, 246
- Superheated vapour pressure, 15, 16
- Supersaturation, 71–72
- Supply branches, 418–419
- Supply design state, 117–139
- Surface adhesion, 474
- Surface contamination, 474
- Surface factor, 188
- Surface temperature of the sun, 141
- Surface tension, 474
- Surging, 337–338
- Sweating, 79
- Synthetic test dusts, 474–475
- System characteristic curves, 425, 426
- System dampers, 437–439
- Temperature gradients, 84–85, 91
- Temperature of adiabatic saturation, 26, 29–31, 39, 51
- Terminal velocity, 473
- Testing for refrigerant leaks, 343
- Test pressure, 340

- Thermistor, 350
 Thermocouples, 350
 Thermodynamic
 system, 233
 wet-bulb temperature, 26
 Thermodynamics, 233
 first law of, 233
 second law of, 233
 Thermo-regulatory system, 79–80
 Thermostatic expansion valve, 309–311
 Thermosyphon cooling, 255, 287
 Three port diverting valves, 368–369
 Three port mixing valves, 368–369
 Threshold limit value, 451, 452
 Throttling expansion, 235
 Throttling range, 359
 Thunderstorms, 100
 Timed two-position control, 356
 Time lag, 176–179, 188, 348, 349
 Tornadoes, 100
 Total fan efficiency, 130, 401
 Total pressure, 401, 402
 Total sensory pollution, 456
 Total time lag, 348–349
 Trade Winds, 99–100
 Transient energy, 233
 Transition pieces, 408–411
 Transitional airflow, 393
 Transmission of solar radiation through glass,
 158–160
 Transmissivity of glass, 158, 159
 Triple point, 34, 35
 Tube erosion, 315
 Tube-in-tube condensers, 341
 Tube withdrawal for condensers, 341
 Turbulent airflow in ducts, 392–396
 Turn-down ratio, 370
 Turning vanes, 416, 418
 Two-position control, 356

 Undershoot, 347, 357
 Universal gas constant, 11
 U-value
 for cooler coils, 273, 277
 for duct walls, 189

 Valves, 362–370
 authority, 363–367, 370
 capacity index, 370
 characteristics, 365
 flow coefficient, 370
 stem positioners, 370

 Van der Waals forces, 474
 Vapour
 absorption refrigeration, 380–391
 absorption system control, 389
 absorption system steam pressures, 389
 compression cycle, 232, 246–249
 compression refrigeration, 231–232
 correction factor, 102
 pressure, 14, 15, 16
 Vapours, 4
 Variable inlet guide vanes, 337–338, 437,
 439–440
 Variation of fan capacity, 437–441
 Vaso-constriction, 80
 Vaso-dilation, 79
 Velocity
 method of duct sizing, 396–398
 pressure, 392, 401, 403
 profiles, 433
 Vena contracta, 404–406
 Venetian blinds, 161–164, 181, 184, 187
 Ventilation, 450–465
 Ventilation effectiveness factor, 454
 Virial coefficients, 7, 31–33
 Viruses, 473
 Viscosity, 392, 394, 395
 Viscous airflow in ducts, 392–396
 Viscous filters, 479–480
 Volatiles emitted from furnishings, 452
 Volume transfer coefficient, 300
 Volumetric efficiency, 253–255

 Wall heat gain, 172–179
 Wall-solar azimuth, 143
 Warm air supply temperatures, 138–139
 Water chillers, 325–331
 Water-cooled condenser, 295
 Water injection, 53–55
 Water vapour, 6, 12, 13, 14
 Westerlies, 100
 Wet-bulb temperature, 26–29, 90, 107
 Wet filters, 484–485
 Wet resultant temperature, 89
 Wettability, 483
 Wet vapour, 235
 Wild cooler coil, 284
 Wind chill index, 89
 Window frame, 167
 Winds, 99–100
 Work, 233
 Work done in compression, 239–241